LC 205

OIL-LUBRICATED ROTARY VANE VACUUM PUMP

TECHNICAL DATA

		LC 205
Part number		9603040
Frequency	**Hz**	50 60
Nominal flow rate	**m³/h**	205 245
Final pressure Gas Ballast closed	**mbar (Abs)**	0.1
Final pressure Gas Ballast open	**mbar (Abs)**	0.5
Max inlet pressure for Gas Ballast open water vapour	**mbar (Abs)**	25
Max water vapour pumping rate Gas Ballast open	**kg/h**	3,5
Continuous operating range	**mbar (Abs)**	400 ÷ 0,1
Maximum inlet air temperature	**°C**	40
Oil type		SW 100
Oil capacity (Min - Max)	**dm³**	4 ÷ 5
Noise level (UNI EN ISO 2151±3dB)	**dB(A)**	70 73
Weight	**kg**	170

27/10/2026 10:16 Subject to change without notice

CURVES





NOTE: Curves refer to suction pressure and temperature of 20°C (tolerance ±10%)

LC 205

OIL-LUBRICATED ROTARY VANE VACUUM PUMP

DIMENSIONS



MOTORS

LC 205 [3 Phase]						
ID	**POWER [kW]**	**VOLTAGE [V]**	**FREQUENCY [Hz]**	**EFFICIENCY**	**RPM**	**Notes**
SF	5,5 5,5	Δ230/Y400 Δ265/Y460	50 60	IE3	1400 1700	
SL	5,5 6,6 6,6	YY190-200/Y380-400 YY208-230/Y460 YY200-220/Y400-440	50 60 60	IE3 IE3 -	1400 1700 1700	UL

27/10/2026 10:16 Subject to change without notice

LC 205

OIL-LUBRICATED ROTARY VANE VACUUM PUMP



ACCESSORIES

		PART NUMBER
1	Nut	0202004
2	Reducer	2001012
3	Reducer	2001017
4	Elbow fitting	2101002
5	Elbow	2101018
6	Hose barb fitting ATG	2103016
7	T Fitting	2106047
8	Nipples	2201007
9	FCM Filter	9001019
10	VMR Vacuum Gauge	9009003
11	Oil level minimum electrical kit (N.C.)	9013014
12	Oil level minimum electrical kit (N.O.)	9013015
13	Filter clogging pressure gauge SIF	9014003
14	Clogged SIF filter switch	9019001
15	Sensor kit	9021003

VARIANTS

PFPE	Applications with over-concentration of Oxygen

27/10/2026 10:16 Subject to change without notice